

The `runcode` package

Haim Bar and HaiYing Wang
haim.bar@uconn.edu, haiying.wang@uconn.edu

August 21, 2022

Abstract

`runcode` is a \LaTeX package that executes programming source codes (including all command line tools) from \LaTeX , and embeds the results in the resulting pdf file. Many programming languages can be easily used and any command-line executable can be invoked when preparing the pdf file from a tex file. `runcode` is also available on [CTAN](#).

It is recommended to use this package in the server mode together with the [Python talk2stat](#) package. Currently, the server mode supports [Julia](#), [MatLab](#), [Python](#), and [R](#). More languages will be added.

For more details and usage examples and troubleshooting, refer to the package's github repository, at <https://github.com/Ossifragus/runcode>.

1 Installation

You can simply put the `runcode.sty` file in the \LaTeX project folder.

The server mode requires the `talk2stat` package. To install it from the command line, use:

```
pip3 install talk2stat
```

Note: `runcode` requires to enable the `shell-escape` option when compiling a \LaTeX document.

2 Usage

2.1 Load the package:

```
\usepackage[options]{runcode}
```

Available options are:

- `cache`: use cached results.
- `julia`: start server for [Julia](#) (requires `talk2stat`).
- `matlab`: start server for [MatLab](#) (requires `talk2stat`).
- `nominted`: use the `fvextra` package instead of the `minted` package to show code (this does not require the `pygments` package, but it does not provide syntax highlights).

- `nohup`: use the `nohup` command when starting a server. When using the server-mode, some editors terminate all child processes after \LaTeX compiling such as Emacs with Auctex. This option set the variable `notnohup` to be false, and the server will not be terminated by the parent process. **This option has to be declared before declaring any language**, e.g., `[nohup, R]` works but `[R, nohup]` does not work.
- `python`: start server for Python (requires `talk2stat`).
- `run`: run source code.
- `R`: start server for R (requires `talk2stat`).
- `stopserver`: stop the server(s) when the pdf compilation is done.

Note: If `minted` is used, the style of the code block is controlled through the `minted` package, e.g.:

```
\setminted[julia]{linenos, frame=single, bgcolor=bg, breaklines=true}
\setminted[R]{linenos, frame=single, bgcolor=lightgray, breaklines=true}
```

The outputs from executing codes are displayed in `tcolorbox`, so the style can be customized with `\tcbsset`, e.g.:

```
\tcbsset{breakable,colback=red!5!white,colframe=red!75!black}
```

2.2 Basic commands:

- `\runExtCode{Arg1}{Arg2}{Arg3}[Arg4]` runs an external code.
 - `Arg1` is the executable program.
 - `Arg2` is the source file name.
 - `Arg3` is the output file name (with an empty value, the counter `codeOutput` is used).
 - `Arg4` controls whether to run the code. `Arg4` is optional with three possible values: if skipped or with empty value, the value of the global Boolean variable `runcode` is used; if the value is set to `run`, the code will be executed; if set to `cache` (or anything else), use cached results (see more about the cache below).
- `\showCode{Arg1}{Arg2}[Arg3][Arg4]` shows the source code, using `minted` for a pretty layout or `fvextra` (if `pygments` is not installed).
 - `Arg1` is the programming language.
 - `Arg2` is the source file name.
 - `Arg3` is the first line to show (optional with a default value 1).
 - `Arg4` is the last line to show (optional with a default value of the last line).
- `\includeOutput{Arg1}[Arg2]` is used to embed the output from executed code.

- `Arg1` is the output file name, and it needs to have the same value as that of `Arg3` in `\runExtCode`. If an empty value is given to `Arg1`, the counter `codeOutput` is used.
- `Arg2` is optional and it controls the type of output with a default value `vbox`
 - * `vbox` (or `skipped`) = verbatim in a box.
 - * `tex` = pure latex.
 - * `inline` = embed result in text.
- `\inln{Arg1}{Arg2}[Arg3]` is designed for simple calculations; it runs one command (or a short batch) and displays the output within the text.
 - `Arg1` is the executable program or programming language.
 - `Arg2` is the source code.
 - `Arg3` is the output type.
 - * `inline` (or `skipped` or with empty value) = embed result in text.
 - * `vbox` = verbatim in a box.

2.3 Language specific shortcuts:

Julia

- `\runJulia[Arg1]{Arg2}{Arg3}[Arg4]` runs an external **Julia** code file.
 - `Arg1` is optional and uses `talk2stat`'s **Julia** server by default.
 - `Arg2`, `Arg3`, and `Arg4` have the same effects as those of the basic command `\runExtCode`.
- `\inlnJulia[Arg1]{Arg2}[Arg3]` runs **Julia** source code (`Arg2`) and displays the output in line.
 - `Arg1` is optional and uses the **Julia** server by default.
 - `Arg2` is the **Julia** source code to run. If the **Julia** source code is wrapped between `""` on both sides (as in the markdown grammar), then it will be implemented directly; otherwise the code will be written to a file on the disk and then be called.
 - `Arg3` has the same effect as that of the basic command `\inln`.

MatLab

- `\runMatLab[Arg1]{Arg2}{Arg3}[Arg4]` runs an external **MatLab** code file.
 - `Arg1` is optional and uses `talk2stat`'s **MatLab** server by default.
 - `Arg2`, `Arg3`, and `Arg4` have the same effects as those of the basic command `\runExtCode`.
- `\inlnMatLab[Arg1]{Arg2}[Arg3]` runs **MatLab** source code (`Arg2`) and displays the output in line.
 - `Arg1` is optional and uses the **MatLab** server by default.

- `Arg2` is the **MatLab** source code to run. If the **MatLab** source code is wrapped between `""` on both sides (as in the markdown grammar), then it will be implemented directly; otherwise the code will be written to a file on the disk and then be called.
- `Arg3` has the same effect as that of the basic command `\inln`.

Python

- `\runPython[Arg1]{Arg2}{Arg3}[Arg4]` runs an external **Python** code file.
 - `Arg1` is optional and uses **talk2stat**'s **Julia** server by default.
 - `Arg2`, `Arg3`, and `Arg4` have the same effects as those of the basic command `\runExtCode`.
- `\inlnPython[Arg1]{Arg2}[Arg3]` runs **Python** source code (`Arg2`) and displays the output in line.
 - `Arg1` is optional and uses the **Python** server by default.
 - `Arg2` is the **Julia** source code to run. If the **Python** source code is wrapped between `""` on both sides (as in the markdown grammar), then it will be implemented directly; otherwise the code will be written to a file on the disk and then be called.
 - `Arg3` has the same effect as that of the basic command `\inln`.
- `\runPythonBatch[Arg1][Arg2]` runs an external **Python** code file in batch mode (without a server running). Python (at least currently), unlike the other languages we use, does not have an option to save and restore a session, which means that once a Python session ends, the working environment (variable, functions) is deleted. In order to allow a batch-mode in Python, we implemented such capability. It requires the **dill** module, which has to be installed via `pip3 install dill`.
 - `Arg1` is the **Python** source file name,
 - `Arg2` is the output file name.

R

- `\runR[Arg1]{Arg2}{Arg3}[Arg4]` runs an external **R** code file.
 - `Arg1` is optional and uses **talk2stat**'s **R** server by default.
 - `Arg2`, `Arg3`, and `Arg4` have the same effects as those of the basic command `\runExtCode`.
- `\inlnR[Arg1]{Arg2}[Arg3]` runs **R** source code (`Arg2`) and displays the output in line.
 - `Arg1` is optional and uses the **R** server by default.
 - `Arg2` is the **R** source code to run. If the **R** source code is wrapped between `""` on both sides (as in the markdown grammar), then it will be implemented directly; otherwise the code will be written to a file on the disk and then be called.
 - `Arg3` has the same effect as that of the basic command `\inln`.

3 Revisions

- v1.7, August 20, 2022: changed the tmp/ folder to generated/ in order to conform with CTAN suggestions; renamed the troubleshooting file.
- v1.6, August 10, 2022: stop only configured/running servers; a new reducedspace option - some document classes put more space after the code box; changed the default timeout of servers to 60 seconds; expanded the troubleshooting document. New examples are now available on GitHub, including how to collaborate with people who use Overleaf.
- v1.5, July 23, 2022: Removed the utf8x option when loading inputenc due to a conflict with hyperref.
- v1.4, July 18, 2022: Fixed a bug in the cache mode.
- v1.3, May 14, 2022: Removed the hard-coded minted options.
- v1.2, May 3, 2022: Added python options (server and batch).
- v1.1, April 17, 2021: Added a nohup option; improved error handling (missing code files, zero bytes in output files.)

4 Contributing

We welcome your contributions to this package by opening issues on GitHub and/or making a pull request. We also appreciate more example documents written using `runcode`.

Citing `runcode`: Haim Bar and HaiYing Wang (2021). [Reproducible Science with L^AT_EX](#), *Journal of Data Science* 2021; 19, no. 1, 111-125, DOI 10.6339/21-JDS998